




**The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ**

PCT

An Executive Agency of the Department of Trade and Industry

Patents Form 1/77

Patents Act 1977
(Rule 16)040CT02 E753335-1 000602
P01/7700 0.00-0223025.8**Request for grant of a patent**

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

1. Your reference

DMC/MP/P9878.GB

2. Patent application number

(The Patent Office will fill in this part)

0223025.8

04 OCT 2002

3. Full name, address and postcode of the or of each applicant (*underline all surnames*)GERARD FRANCIS ROBINSON
26 Upper Churchtown Road
Churchtown
Dublin 14
IrelandPatents ADP number (*if you know it*)

If the applicant is a corporate body, give the country/state of its incorporation

0716392602

4. Title of the invention

SEALING SYSTEM

5. Name of your agent (*if you have one*)"Address for service" in the United Kingdom to which all correspondence should be sent (*including the postcode*)MACLACHLAN & DONALDSON (UNITED KINGDOM)
LIMITED
T/A ANSONS
240 Upper Newtownards Road
Belfast
Northern Ireland
United Kingdom BT4 3EUPatents ADP number (*if you know it*)

08473401001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (*if you know it*) the or each application number

Country

Priority application number
(*if you know it*)Date of filing
(*day / month / year*)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(*day / month / year*)8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (*Answer 'Yes' if*

NO

a) any applicant named in part 3 is not an inventor, or
b) there is an inventor who is not named as an applicant, or

c) any named applicant is a corporate body.

See note (d))

Patents Form 1/77

0049056 04-Oct-02 03:34

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form.
Do not count copies of the same document

Continuation sheets of this form

Description	7
Claim(s)	2
Abstract	-
Drawing(s)	4 only

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 8/77) 1

Request for substantive examination (Patents Form 10/77)

Any other documents
(please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature

Date 4/10/2002

DENIS A. MCCARTHY,
MACLACHLAN & DONALDSON (UNITED KINGDOM)

12. Name and daytime telephone number of person to contact in the United Kingdom

+44(0) 28 9065 6103 BRUCE ROBERTSON /
JOHN HANNA

LIMITED

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

1

SEALING SYSTEM

The present invention relates to a sealing system for sealing the joint between two contiguous surfaces disposed at an angle to each other, such as, but not limited to the horizontal joint
5 between a wall and a shower tray or bath.

The main prior art methods of sealing the junction of walls and horizontal surfaces (such as shower trays, baths and worktops) are as follows.

10 METHOD A: A Semi-rigid substantially L profiled sealing strip with flexible sealing lips attached to the upper most and/or outer most boundaries is installed against the vertical surface to form a pressure seal with horizontal surface as described by GB 2136288A.

METHOD B: A sealant material (typically silicone) is extruded into over the joint.

15

METHOD C: A multi-part interlocking longitudinal strip (with corner accessories) is combined with a sealing material to form a telescopic seal between the horizontal and vertical surfaces as listed by GB 2289924 GB 2320068

20 METHOD D: A longitudinal strip with an incorporated sealant bond breaker is combined with a sealing material to form an elastic seal between the horizontal and vertical surfaces, as listed by EP 1112418

25 METHOD E: A longitudinal angular interlocking strip with a flexible sealing lip is combined with an adhesive tape whereby the strip has a detachably lockable T shaped head to form a release mechanism to accommodate joint movement as listed by US 4829731.

METHOD F: A longitudinal substantially L shaped strip incorporates a third limb to reduce the volume of sealing material required to seal the joint. Sealing material is applied into the
30 strip accordingly to form a seal as listed by GB 2348805

The main disadvantages of the above arrangements are that in the case of method A, soft lips perish, shrink, harden and leak in shower areas and as the joint expands the sealing lip loses pressure. In the case of B the exposed sealant is unsightly and often de-bonds or tears under wall movement. The overlapping strips in method C created an unattractive joint line and the butt jointed corner detail may present problems if one wall moves relative to the other. The flexible fin in method E forms the seal and this sealing lip deteriorates in the shower environment. The third limb detailed in method F is incorporated to reduce the volume of sealant required to seal the joint and not to accommodate joint movement.

10

It is the object of this invention to provide a sealing system that may substantially reduce the aforementioned problems.

According to the present invention there is a sealing system comprising of at least two parts being a semi-flexible longitudinal strip profile and a sealing material both adapted in combination to maintain a sealed joint between typically relatively vertical and horizontal surfaces whereby the strip profile comprising of a first upper limb having an upper limb upper boundary and an upper limb lower boundary between which there extends an upper limb inner face and an upper limb outer face, and from which upper limb inner face and/or upper limb boundaries there extends at least one second outer limb having an outer limb inner boundary attached to the upper limb and an outer limb outer boundary between which outer limb boundaries there extends an outer limb upper face and an outer limb lower face, whereby there extends from the upper limb inner face and/or the upper limb lower boundary and/or the outer limb lower face and/or the outer limb outer boundary, at least a third inner limb and/or filler material adapted to sealingly engage an uncured sealing material and to aid the full or substantial isolation of the uncured sealing material from the upper limb inner face and/or the outer limb lower face.

Preferably, flexibility in the strip profile may be achieved through adjusting the sectional wall thickness and/or or co-extruding flexible material at selected points in the strip profile.

Preferably, the inner limb and/or filler material may form and/or anchor a sealant reservoir and/or directly engage the sealing material with the horizontal surface in substantial isolation from the remainder of the strip profile.

5

Alternatively, additional inner limbs and/or filler material may extend and/or connect together from the upper limb inner face or upper limb lower boundary and/or the outer limb lower face or outer limb outer boundary.

10. Preferably, that part of the strip profile in contact with sealing material being typically at the interface between the strip and the horizontal and vertical surfaces has a plurality of ribs and/or recesses and/or barbs and/or holes to contact and grip a sealing material and/or an adhesive material.

15. Ideally, the outer limb upper face is adapted to throw off water over the complementary sealing material.

- In one embodiment the strip may have a flexible lip along the uppermost boundary of the upper limb and the outer most boundary of the outer limb adapted to engage irregular vertical and horizontal surfaces respectively and make the joint more attractive.
- 20

Furthermore, the height of the first limb may be reduced through the provision of a least one score line allowing the easy tearing off of a longitudinal section of strip.

25. The invention will be generally described with reference to the accompanying drawings:-

Figure 1 represents a sectional view of a semi-flexible longitudinal strip profile according to the current invention.

4

Figure 2 represents a sectional view of the semi-flexible longitudinal strip profile detailed in figure 1 when installed over a joint between a vertical and horizontal surface. A reservoir of sealing material, typically silicon is substantially isolated from the upper limb and outer limb engages the inner limb and the horizontal surface.

5

Figure 3 represents a sectional view of an alternative semi-flexible longitudinal strip profile according to the current invention.

Figure 4 represents a sectional view of the semi-flexible longitudinal strip profile detailed in figure 3 when installed over a joint between a vertical and horizontal surface. A reservoir of sealing material substantially isolated from the upper limb and outer limb engages the third limb and the horizontal surface.

Figure 5 represents a sectional view of an alternative embodiment of the semi-flexible longitudinal strip profile whereby flexible co-extrusions connect the inner limb with the upper limb and outer limb.

Figure 6 represents a sectional view of an alternative embodiment of the semi-flexible longitudinal strip profile detailed in figure 2. A reservoir of sealing material substantially isolated from the upper limb and outer limb engages two inner limbs and the horizontal surface.

Figure 7 represents a sectional view of an alternative embodiment of the semi-flexible longitudinal strip profile whereby the strip is detachably self interlocking.

25

Figure 8 represents the profile detailed in figure 7 after it is interlocked and installed over a joint.

5

The invention will hereinafter be more particularly described with reference to the accompanying drawings, which show by way of example only, embodiments of the seal according to the invention, in these drawings -:

- 5 Figure 1 details a sectional view of a strip profile 10 which has an upper limb 11 having an upper limb upper boundary 12 and a upper limb lower boundary 13 between which there extends an upper limb outer face 14 adapted through a series of ridges 15 and recesses 16 to accommodate and grip an adhesive or sealing material it may engage with a vertical surface A (fig2). The height of the upper limb 11 may be easily reduced through the provision of at least one score line 28 running parallel to the lower boundary 13.

- 10 The upper limb 11 has an upper limb inner face 17 from which there extends an outer limb 18 having an outer limb inner boundary 19 attached to the upper limb inner face 17 and an outer limb outer boundary 33 between which there extends an outer limb upper face 20 adapted to throw off water.

- 15 The outer limb 18 has an outer limb lower face 21 from which there extends an inner limb 22 having an inner limb inner boundary 23 attached to the outer limb inner face 21 and an inner limb outer boundary 24 between which there extends an inner limb upper face 25 and an inner limb lower face 26 adapted to engage and grip a sealing material 30 (fig 2) through the provision of one or more ribs 27.

- 20 Figure 2 details a sectional view the strip profile described in figure 1 when installed over a joint defined where vertical surface A (typically a wall) meets a horizontal surface B (typically a shower tray or bath ledge). A section of the strip profile along score line 29 has been removed and the strip profile upper limb 11 has been adapted through the provision of holes 31 to accommodate adhesive (typically tile adhesive).

- 25 The sealant 30 is solidly engaged by inner limb 22 but substantially isolated from upper limb 11 and outer limb 18. Upper limb 11 and outer limb 18 are semi flexible and in the event of

horizontal surface B moving down (typically caused by acrylic bath deflection or timber floor joist shrinkage) or the vertical surface moving back (typically caused by timber stud wall shrinkage) the outer limb 18 will deflect substantially about the axis neck 32 because this limb is not installed under tension.

5

The sealant 30 and the inner limb 22 are substantially free to move down with the horizontal surface B and the upper limb 11 is substantially free to move back with the vertical surface A. The junction 23 of meeting limbs 18 and 22 is positioned to eliminate or minimize the risk of a gap developing between the outer limb outer boundary 33 and the horizontal surface B in the event of horizontal surface B moving down.

10

Figure 3 and figure 4 details sectional views of a strip profile similar to that described in figure 1 and figure 2 respectively.

15 In figures 3 and 4 the outer limb 34 and inner limb 35 are more substantially curved than those in figures 1 and 2 respectively to accommodate installations where a wider unobtrusive strip is required (typically to span a gap between the horizontal and vertical surfaces). The dynamics that create the capability for joint movement are still incorporated into the strip profile. The stress on outer limb 34 created by joint movement is more evenly distributed over the length of the limb rather than a specific part as in 32 (fig 2).

20

In figure 4 a section of the strip profile along score line 29 has been removed and the strip profile upper limb 11 has been adapted through the provision of holes 31 to accommodate adhesive (typically tile adhesive).

25

Figure 5 is one embodiment of the invention where the inner limb 37 is attached to the upper limb 11 and the outer limb 34. The introduction of one or more flexible co-extrusions 35 and 36 creates stress release points in the event of joint movement. It should be understood that limb 34 may in various embodiments be attached to the upper most or lowermost boundaries

7

of upper limb 11 (not shown). A flexible fin (not shown) can be co-extruded along the outer boundary 40 of outer limb 34 to accommodate irregular surfaces.

5 Figure 6 is another embodiment of the invention wherein two inner limbs 38 and 39 substantially isolate the sealing material from upper limb 11 and outer limb 18. A flexible lip 50 is attached to the outer limb outer boundary.

10 Figure 7 and 8 details yet another embodiment of this invention whereby the strip profile is self interlocking through a flexible co-extrusion 45 connecting the outer limb lower face 46 to the inner limb 47. The inner limb 47 outer boundary 48 engages chamber 49 formed by limb 50 with upper limb 11 and this stabilizes inner limb 47 while cutting miters for meeting strips at corners. In this embodiment the stress on the strip profile is substantially released through the flexibility of the co-extrusion 45 and the easy release of the inner limb outer boundary 48 from the chamber 49.

15

CLAIMS:

1. A sealing system comprising of at least two parts being a semi-flexible longitudinal strip profile and a sealing material both adapted in combination to maintain a sealed joint between typically relatively vertical and horizontal surfaces whereby the strip profile comprising of a first upper limb having an upper limb upper boundary and an upper limb lower boundary between which there extends an upper limb inner face and an upper limb outer face, and from which upper limb inner face and/or upper limb boundaries there extends at least one second outer limb having an outer limb inner boundary attached to the upper limb and an outer limb outer boundary between which outer limb boundaries there extends an outer limb upper face and an outer limb lower face, whereby there extends from the upper limb inner face and/or the upper limb lower boundary and/or the outer limb lower face and/or the outer limb outer boundary, at least a third inner limb and/or filler material adapted to sealingly engage an uncured sealing material and to aid the full or substantial isolation of the uncured sealing material from the upper limb inner face and/or the outer limb lower face.
2. A sealing system as claimed in claim 1, wherein flexibility in the strip profile may be achieved through adjusting the sectional wall thickness and/or or co-extruding flexible material at selected points in the strip profile.
3. A sealing system as claimed in any one of the preceding claims, wherein the inner limb and/or filler material may form and/or anchor a sealant reservoir and/or directly engage the sealing material with the horizontal surface in substantial isolation from the remainder of the strip profile.
4. A sealing system as claimed in any one of the preceding claims, wherein additional inner limbs and/or filler material may extend and/or connect together from the upper limb inner face or upper limb lower boundary and/or the outer limb lower face or outer limb outer boundary.

9

5. A sealing system as claimed in any one of the preceding claims, wherein that part of the strip profile in contact with sealing material being typically at the interface between the strip and the horizontal and vertical surfaces has a plurality of ribs and/or recesses and/or barbs and/or holes to contact and grip a sealing material and/or an adhesive material.

5

6. A sealing system as claimed in any one of the preceding claims, wherein the outer limb upper face is adapted to throw off water over the complementary sealing material.

7. A sealing system as claimed in any one of the preceding claims, wherein the strip may have a flexible lip along the uppermost boundary of the upper limb and the outer most boundary of the outer limb adapted to engage irregular vertical and horizontal surfaces respectively and make the joint more attractive.

8. A sealing system as claimed in any one of the preceding claims, wherein the height of the first limb may be reduced through the provision of a least one score line allowing the easy tearing off of a longitudinal section of strip.

9. A sealing system substantially in accordance with any of the embodiments as herein described with reference to and as shown in the accompanying drawings.




FIG. 1






FIG. 2



3/4





FIG. 7





FIG. 8



**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☐ BLACK BORDERS

☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES

☒ FADED TEXT OR DRAWING

☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING

☐ SKEWED/SLANTED IMAGES

☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS

☐ GRAY SCALE DOCUMENTS

☐ LINES OR MARKS ON ORIGINAL DOCUMENT

☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.